



## Pro Audio 31

<b>treble</b>	silk calotte, 25 mm
<b>bass</b>	polypropylene cone, 95 mm
<b>cross over</b>	4500 Hz
<b>sensitivity</b>	0,7V 0- +10dB
<b>maximum acoustic output short term RMS @ 1m</b>	105 dB SPL
<b>maximum acoustic output peak per pair @ 1m</b>	111 dB SPL
<b>frequency response</b>	70-22000 Hz +/- 3 dB
<b>amplifier treble</b>	40W
<b>amplifier bass</b>	40W
<b>volume adjustment</b>	0- +10 dB (stepless)
<b>magnetic shielding</b>	yes
<b>overload protection</b>	yes
<b>radio frequency shielding</b>	optional
<b>auto stand-by</b>	yes
<b>stand-by latency</b>	3 min
<b>signal input</b>	1 RCA
<b>signal output</b>	none
<b>power inlet</b>	230V AC
<b>power cord</b>	included
<b>weight</b>	2,1 kg
<b>cabinet</b>	closed
<b>dimensions (WxHxD)</b>	110x175x145 mm
<b>black</b>	MDF
<b>white</b>	MDF
<b>silver</b>	MDF
<b>birch</b>	massive birch
<b>cherry</b>	stained massive birch
<b>custom colors</b>	on request
<b>accessories</b>	
<b>metal grille</b>	optional
<b>soft grille</b>	n.a.
<b>wall mounting</b>	optional
<b>microphone-stand adapter</b>	optional
<b>floor stand</b>	optional, matching color
<b>XLR/RCA adapter</b>	not required
<b>radio frequency shielding</b>	optional
<b>warranty</b>	24 months *

\* Profel Oy myöntää kaikille tuotteelleen ostohetkestä lasketun kahden vuoden takuun. Takuu koskee kaiuttimelementit ja kotelon osia valmistusvirheiden ja materiaalivikojen osalta. Lisäksi aktiivikaiutinmallien elektroniikkaosille myönnetään rajattua elinikäistä takuuta.