Pro Audio 40

Active speakers for professional and home entertainment use

The Pro Audio 40 loudspeakers perform large regardless their small size, providing clear and powerful sound wherever professional performance is needed. The units are bi-amplified, self-powered, and equipped with line level analog input connectors (RCA) for perfect compatibility with unbalanced signal sources.

Pro Audio 40 main features:

- Superb sound quality
- High quality components
- Integrated security circuit
- Magnetic shielding
- Gain adjustment
- RCA input
- 24 months warranty



Pro Audio 40, Active 2-way bass-reflex loudspeaker

Bass	125 mm polypropylene cone
Treble	19 mm aluminum calotte
Frequency response	60 - 20 000 Hz +/- 3 dB
Crossover frequency	4,5 kHz
Sensitivity	0,7 V 0 - +10 dB
Maximum acoustic output	Short term RMS @ 1 m 103 dB SPL Peak per pair @ 1 m 109 dB SPL
Amplifier	2 x 50 W RMS per speaker element
Gain adjustment	0 - +10 dB (stepless)
Magnetic shielding	Yes
Colours (MDF cabinet)	Black, white, grey
Connection	RCA
Cabinet	150x245x180 mm (WxHxD)
Weight	4 kg
Accessories	Grille, wall mounting