Pro Studio 65

Active speakers for professional and home entertainment use

The Pro Studio 65 premium quality loudspeakers are designed for near-field monitoring. Powerful performance combined with smooth, truthfully natural sound. The units are selfpowered and each speaker element is individually amplified with a 64 W integrated amplifier. Pro Studio speakers are equipped with line level analog input and output connectors (XLR) for perfect compatibility with balanced signal sources.

Pro Studio 65 main features:

- Superb sound quality
- High quality components
- Integrated security circuit
- Magnetic shielding
- XLR input/output connectors
- 24 months warranty

Pro Studio 65, Active 2-way bass-reflex loudspeaker

Bass	170 mm polypropylene cone
Treble	25 mm silk calotte
Frequency response	45 - 20 000 Hz +/- 3 dB
Crossover frequency	4,5 kHz
Sensitivity	0,7 V 0 +/-6 dB
Maximum acoustic output	Short term RMS @ 1 m 106 dB SPL Peak per pair @ 1 m 112 dB SPL
Amplifier	2 x 64 W RMS per speaker element
Bass tone adjustment	+/- 2 dB
Treble tone adjustment	+/- 2 dB
Bass field adjustment (low bass)	0, -2 dB, -4 dB
Magnetic shielding	Yes
Colours (MDF cabinet)	Black, white
Connectors (in/out)	XLR (Pin 1 = GND, Pin 2 = +, Pin 3 = -)
Cabinet	190x300x225 mm (WxHxD)
Weight	7 kg
Accessories	Grille, wall mounting 24-bit DA-converter with sample-rate converter 110 ohm AES/EBU (XLR)

